



## SAFETY DATA SHEET HOTSPOT Black Paint Aerosols

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name** HOTSPOT Black Paint Aerosols

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Paint.

#### 1.3. Details of the supplier of the safety data sheet

**Supplier** Rustins Ltd  
Waterloo Road  
London  
NW2 7TX  
United Kingdom

#### 1.4. Emergency telephone number

**Emergency telephone** +44 (0)20 8450 4666 (Hours 09:00 - 17:00 Mon to Fri)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (EC 1272/2008)

**Physical hazards** Aerosol 1 - H222, H229

**Health hazards** Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H336 STOT RE 2 - H373

**Environmental hazards** Not Classified

**Human health** Vapours and spray/mists in high concentrations are narcotic. See Section 11 for additional information on health hazards.

**Environmental** The product is not expected to be hazardous to the environment.

**Physicochemical** Containers can burst violently or explode when heated, due to excessive pressure build-up. The product is extremely flammable. Vapours may form explosive mixtures with air.

#### 2.2. Label elements

##### Hazard pictograms



**Signal word**

**Danger**

# HOTSPOT Black Paint Aerosols

<b>Hazard statements</b>	H222 Extremely flammable aerosol. H229 Pressurised container: may burst if heated. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H373 May cause damage to organs through prolonged or repeated exposure.
<b>Precautionary statements</b>	P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P260 Do not breathe spray. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 Call a POISON CENTRE/doctor if you feel unwell. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
<b>Supplemental label information</b>	EUH066 Repeated exposure may cause skin dryness or cracking.
<b>Contains</b>	ACETONE, XYLENE, BUTAN-1-OL
<b>Supplementary precautionary statements</b>	P261 Avoid breathing spray. P264 Wash contaminated skin thoroughly after handling. P314 Get medical advice/ attention if you feel unwell. P321 Specific treatment (see medical advice on this label). P332+P313 If skin irritation occurs: Get medical advice/ attention. P302+P352 IF ON SKIN: Wash with plenty of water. P337+P313 If eye irritation persists: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. P501 Dispose of contents/ container in accordance with national regulations.

## 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

<b>ACETONE</b>		<b>30-60%</b>
CAS number: 67-64-1	EC number: 200-662-2	REACH registration number: 01-2119471330-49-XXXX
<b>Classification</b>		
Flam. Liq. 2 - H225		
Eye Irrit. 2 - H319		
STOT SE 3 - H336		

## HOTSPOT Black Paint Aerosols

<b>PETROLEUM GASES, LIQUEFIED &lt;0.1% 1,3-BUTADIENE</b>	<b>30-60%</b>
CAS number: 68476-85-7	EC number: 270-704-2
<b>Classification</b>	
Flam. Gas 1 - H220	
Press. Gas (Comp.) - H280	
<b>XYLENE</b>	<b>10-30%</b>
CAS number: 1330-20-7	EC number: 215-535-7
	REACH registration number: 01-2119488216-32-XXXX
<b>Classification</b>	
Flam. Liq. 3 - H226	
Acute Tox. 4 - H312	
Acute Tox. 4 - H332	
Skin Irrit. 2 - H315	
Eye Irrit. 2 - H319	
STOT SE 3 - H335	
STOT RE 2 - H373	
Asp. Tox. 1 - H304	
Aquatic Chronic 3 - H412	
<b>ETHYLBENZENE</b>	<b>1-5%</b>
CAS number: 100-41-4	EC number: 202-849-4
	REACH registration number: 01-2119489370-35-XXXX
<b>Classification</b>	
Flam. Liq. 2 - H225	
Acute Tox. 4 - H332	
STOT RE 2 - H373	
Asp. Tox. 1 - H304	
<b>BUTAN-1-OL</b>	<b>1-5%</b>
CAS number: 71-36-3	EC number: 200-751-6
	REACH registration number: 01-2119484630-38-XXXX
<b>Classification</b>	
Flam. Liq. 3 - H226	
Acute Tox. 4 - H302	
Skin Irrit. 2 - H315	
Eye Dam. 1 - H318	
STOT SE 3 - H335, H336	

## HOTSPOT Black Paint Aerosols

<b>2-METHOXY-1-METHYLETHYL ACETATE</b>	<b>&lt;1%</b>
CAS number: 108-65-6	EC number: 203-603-9
	REACH registration number: 01-2119475791-29-XXXX
<b>Classification</b>	
Flam. Liq. 3 - H226	
STOT SE 3 - H336	

  

<b>1-METHOXY-2-PROPANOL</b>	<b>&lt;1%</b>
CAS number: 107-98-2	EC number: 203-539-1
	REACH registration number: 01-2119457435-35-XXXX
<b>Classification</b>	
Flam. Liq. 3 - H226	
STOT SE 3 - H336	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>General information</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
<b>Inhalation</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If in doubt, get medical attention promptly.
<b>Ingestion</b>	Rinse mouth thoroughly with water. Remove person to fresh air and keep comfortable for breathing. Get medical attention.
<b>Skin contact</b>	Wash skin thoroughly with soap and water. Get medical attention promptly if symptoms occur after washing.
<b>Eye contact</b>	Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.
<b>Protection of first aiders</b>	First aid personnel should wear appropriate protective equipment during any rescue.

#### 4.2. Most important symptoms and effects, both acute and delayed

<b>General information</b>	See Section 11 for additional information on health hazards.
----------------------------	--

#### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	Treat symptomatically.
-----------------------------	------------------------

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

<b>Suitable extinguishing media</b>	Foam, carbon dioxide or dry powder.
-------------------------------------	-------------------------------------

#### 5.2. Special hazards arising from the substance or mixture

<b>Specific hazards</b>	Containers can burst violently or explode when heated, due to excessive pressure build-up.
-------------------------	--

#### 5.3. Advice for firefighters

## HOTSPOT Black Paint Aerosols

**Protective actions during firefighting** Use water to keep fire exposed containers cool and disperse vapours. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid inhalation of vapours and contact with skin and eyes. Ensure suitable respiratory protection is worn during removal of spillages in confined areas.

#### 6.2. Environmental precautions

**Environmental precautions** Avoid discharge into drains.

#### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers.

#### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

**Usage precautions** Keep away from heat, sparks and open flame. Read and follow manufacturer's recommendations. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited. Use suitable respiratory protection if ventilation is inadequate.

**Advice on general occupational hygiene** Wash promptly with soap and water if skin becomes contaminated. Do not eat, drink or smoke when using this product.

#### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Protect from freezing and direct sunlight. Store in a dry place. Do not store near heat sources or expose to high temperatures. Keep away from heat, sparks and open flame.

#### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

### SECTION 8: Exposure controls/Personal protection

#### 8.1. Control parameters

##### Occupational exposure limits

##### **ACETONE**

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m<sup>3</sup>

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m<sup>3</sup>

##### **PETROLEUM GASES, LIQUEFIED <0.1% 1,3-BUTADIENE**

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m<sup>3</sup>

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m<sup>3</sup>

##### **XYLENE**

## HOTSPOT Black Paint Aerosols

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m<sup>3</sup>

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m<sup>3</sup>

Sk, Sk

### ETHYLBENZENE

Long-term exposure limit (8-hour TWA): WEL 100 ppm 441 mg/m<sup>3</sup>

Long-term exposure limit (8-hour TWA): WEL 100 ppm 441 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 125 ppm 552 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 125 ppm 552 mg/m<sup>3</sup>

Sk, Sk

### BUTAN-1-OL

Short-term exposure limit (15-minute): WEL 154 mg/m<sup>3</sup> 50 ppm

### 2-METHOXY-1-METHYLETHYL ACETATE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 274 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 100 ppm 548 mg/m<sup>3</sup>

Sk

### 1-METHOXY-2-PROPANOL

Long-term exposure limit (8-hour TWA): WEL 100 ppm 375 mg/m<sup>3</sup>

Long-term exposure limit (8-hour TWA): WEL 100 ppm 375 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 150 ppm 560 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 150 ppm 560 mg/m<sup>3</sup>

Sk, Sk

WEL = Workplace Exposure Limit

Sk = Can be absorbed through the skin.

### ACETONE (CAS: 67-64-1)

<b>DNEL</b>	Workers - Dermal; Long term systemic effects: 186 mg/kg/day
	Workers - Inhalation; Short term local effects: 2420 mg/m <sup>3</sup>
	Workers - Inhalation; Long term systemic effects: 1210 mg/m <sup>3</sup>
<b>PNEC</b>	- Sediment (Freshwater); 30.4 mg/kg
	- Sediment (Marinewater); 3.04 mg/kg
	- marine water; 1.06 mg/l
	- Soil; 29.5 mg/kg

### XYLENE (CAS: 1330-20-7)

<b>DNEL</b>	Consumer - Dermal; Long term systemic effects: 108 mg/kg/day
	Workers - Dermal; Long term systemic effects: 180 mg/kg/day
	Consumer - Inhalation; Short term local effects: 174 mg/m <sup>3</sup>
	Consumer - Inhalation; Short term systemic effects: 174 mg/m <sup>3</sup>
	Workers - Inhalation; Short term systemic effects: 289 mg/m <sup>3</sup>
	Workers - Inhalation; Short term local effects: 289 mg/m <sup>3</sup>
	Consumer - Inhalation; Long term systemic effects: 14.8 mg/m <sup>3</sup>
	Workers - Inhalation; Long term systemic effects: 77 mg/m <sup>3</sup>

## HOTSPOT Black Paint Aerosols

<b>PNEC</b>	<ul style="list-style-type: none"> <li>- Fresh water; 0.327 mg/l</li> <li>- marine water; 0.327 mg/l</li> <li>- Intermittent release; 0.327 mg/l</li> <li>- STP; 6.58 mg/l</li> <li>- Sediment (Freshwater); 12.46 mg/kg</li> <li>- Sediment (Marinewater); 12.46 mg/kg</li> <li>- Soil; 2.31 mg/kg</li> </ul>
-------------	--

### BUTAN-1-OL (CAS: 71-36-3)

<b>DNEL</b>	<p>Consumer - Oral; Long term systemic effects: 3.125 mg/kg/day          Consumer - Inhalation; Long term local effects: 55 mg/m<sup>3</sup>          Workers - Inhalation; Long term local effects: 310 mg/m<sup>3</sup></p>
-------------	---

<b>PNEC</b>	<ul style="list-style-type: none"> <li>- Fresh water; 0.082 mg/l</li> <li>- Sediment (Freshwater); 0.178 mg/kg</li> <li>- Intermittent release; 2.25 mg/l</li> <li>- Sediment (Marinewater); 0.0178 mg/kg</li> <li>- marine water; 0.0082 mg/l</li> <li>- STP; 2476 mg/l</li> <li>- Soil; 0.015 mg/kg</li> </ul>
-------------	--

### 1-METHOXY-2-PROPANOL (CAS: 107-98-2)

<b>DNEL</b>	<p>Consumer - Oral; Long term systemic effects: 3.3 mg/kg/day          Consumer - Dermal; Long term systemic effects: 18.1 mg/kg/day          Consumer - Dermal; Long term systemic effects: 50.6 mg/kg/day          Workers - Inhalation; Short term local effects: 553.5 mg/m<sup>3</sup>          Consumer - Inhalation; Long term systemic effects: 43.9 mg/m<sup>3</sup>          Workers - Inhalation; Long term systemic effects: 369 mg/m<sup>3</sup></p>
-------------	---

<b>PNEC</b>	<ul style="list-style-type: none"> <li>- Fresh water; 10 mg/l</li> <li>- Sediment (Freshwater); 41.6 mg/kg</li> <li>- Intermittent release; 100 mg/l</li> <li>- Sediment (Marinewater); 4.17 mg/kg</li> <li>- marine water; 1 mg/l</li> <li>- Soil; 2.47 mg/kg</li> </ul>
-------------	---

## 8.2. Exposure controls

<b>Eye/face protection</b>	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible.
<b>Hand protection</b>	No specific requirements are anticipated under normal conditions of use.
<b>Other skin and body protection</b>	Wear suitable protective equipment for prolonged exposure and/or high concentrations of vapours, spray or mist.
<b>Respiratory protection</b>	No specific recommendations. If ventilation is inadequate, suitable respiratory protection must be worn.

## **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Aerosol.
<b>Colour</b>	Black.
<b>Odour</b>	Solvent.

## HOTSPOT Black Paint Aerosols

<b>Odour threshold</b>	No information available.
<b>pH</b>	No information available.
<b>Melting point</b>	No information available.
<b>Initial boiling point and range</b>	-41 (-41 TO 143)°C
<b>Flash point</b>	-40°C Closed cup.
<b>Evaporation rate</b>	No information available.
<b>Evaporation factor</b>	No information available.
<b>Flammability (solid, gas)</b>	No information available.
<b>Upper/lower flammability or explosive limits</b>	Lower flammable/explosive limit: 0.8 % Upper flammable/explosive limit: 13.1 %
<b>Vapour pressure</b>	No information available.
<b>Vapour density</b>	No information available.
<b>Relative density</b>	0.783
<b>Solubility(ies)</b>	Insoluble in water.
<b>Partition coefficient</b>	No information available.
<b>Auto-ignition temperature</b>	270°C
<b>Decomposition Temperature</b>	No information available.
<b>Viscosity</b>	No information available.
<b>Explosive properties</b>	No information available.
<b>Oxidising properties</b>	No information available.
<b><u>9.2. Other information</u></b>	
<b>Other information</b>	None.

### SECTION 10: Stability and reactivity

#### **10.1. Reactivity**

**Reactivity** No test data specifically related to reactivity available for this product or its ingredients.

#### **10.2. Chemical stability**

**Stability** The product may not be stable under some conditions of storage or use.

#### **10.3. Possibility of hazardous reactions**

**Possibility of hazardous reactions** None known.

#### **10.4. Conditions to avoid**

**Conditions to avoid** Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high temperatures or direct sunlight.

#### **10.5. Incompatible materials**

**Materials to avoid** None known.

#### **10.6. Hazardous decomposition products**



## HOTSPOT Black Paint Aerosols

**Hazardous decomposition products**      None at ambient temperatures.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

##### Acute toxicity - oral

ATE oral (mg/kg)                      34,530.39

##### Acute toxicity - dermal

ATE dermal (mg/kg)                    8,450.15

##### Acute toxicity - inhalation

ATE inhalation (vapours mg/l)      76.04

**Inhalation**                              May cause drowsiness or dizziness. Vapours in high concentrations are narcotic. Vapours may cause headache, fatigue, dizziness and nausea.

**Skin contact**                            Causes skin irritation. Repeated exposure may cause skin dryness or cracking.

**Eye contact**                             Causes serious eye irritation.

**Acute and chronic health hazards**                                      May cause damage to organs through prolonged or repeated exposure.

**Route of exposure**                      Inhalation Skin and/or eye contact

#### Toxicological information on ingredients.

#### ACETONE

##### Acute toxicity - oral

Acute toxicity oral (LD<sub>50</sub> mg/kg)      5,800.0

Species                                      Rat

ATE oral (mg/kg)                        5,800.0

##### Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub> mg/kg)    7,800.0

Species                                      Rabbit

ATE dermal (mg/kg)                      7,800.0

##### Acute toxicity - inhalation

Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l)    21.0

Species                                      Rat

ATE inhalation (vapours mg/l)        21.0

#### XYLENE

##### Acute toxicity - oral

## HOTSPOT Black Paint Aerosols

Acute toxicity oral (LD<sub>50</sub> mg/kg) 4,300.0

Species Rat

ATE oral (mg/kg) 4,300.0

### Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub> mg/kg) 3,200.0

Species Rabbit

ATE dermal (mg/kg) 1,100.0

### Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 11.0

## ETHYLBENZENE

### Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 11.0

## BUTAN-1-OL

### Acute toxicity - oral

Acute toxicity oral (LD<sub>50</sub> mg/kg) 2,001.0

Species Rat

ATE oral (mg/kg) 500.0

### Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub> mg/kg) 3,430.0

Species Rabbit

ATE dermal (mg/kg) 3,430.0

### Acute toxicity - inhalation

Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l) 20.1

Species Rat

ATE inhalation (vapours mg/l) 20.1

## 1-METHOXY-2-PROPANOL

### Acute toxicity - oral

Acute toxicity oral (LD<sub>50</sub> mg/kg) 5,660.0

Species Rat

## HOTSPOT Black Paint Aerosols

ATE oral (mg/kg)	5,660.0
<u>Acute toxicity - dermal</u>	
Acute toxicity dermal (LD <sub>50</sub> mg/kg)	13,000.0
Species	Rabbit
ATE dermal (mg/kg)	13,000.0
<u>Acute toxicity - inhalation</u>	
Acute toxicity inhalation (LC <sub>50</sub> vapours mg/l)	54.6
Species	Rat
ATE inhalation (vapours mg/l)	54.6

### SECTION 12: Ecological information

#### 12.1. Toxicity

##### Ecological information on ingredients.

#### ACETONE

##### Acute aquatic toxicity

Acute toxicity - fish	EC <sub>50</sub> , 96 hours: 8300 mg/l, Lepomis macrochirus (Bluegill)
Acute toxicity - aquatic invertebrates	EC <sub>50</sub> , : 8800 mg/l, Daphnia magna

#### XYLENE

##### Acute aquatic toxicity

Acute toxicity - fish	LOEC, : >1 - <10 mg/l, Fish
Acute toxicity - aquatic plants	LOEC, : >1 - <10 mg/l, Algae

#### BUTAN-1-OL

##### Acute aquatic toxicity

Acute toxicity - fish	LC <sub>50</sub> , 96 hours: 1376 mg/l, Pimephales promelas (Fat-head Minnow)
Acute toxicity - aquatic invertebrates	LC <sub>50</sub> , 96 hours: 1328 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC <sub>50</sub> , 96 hours: 225 mg/l, Selenastrum capricornutum

#### 1-METHOXY-2-PROPANOL

##### Acute aquatic toxicity

Acute toxicity - fish	LC <sub>50</sub> , 96 hours: 20800 mg/l, Pimephales promelas (Fat-head Minnow)
Acute toxicity - aquatic invertebrates	EC <sub>50</sub> , 48 hours: 23300 mg/l, Daphnia magna

# HOTSPOT Black Paint Aerosols

**Acute toxicity - aquatic plants**      EC<sub>50</sub>, : 1001 mg/l, Sclenastrum capricornutum

## 12.2. Persistence and degradability

**Persistence and degradability** No data available.

## 12.3. Bioaccumulative potential

**Partition coefficient** No information available.

## 12.4. Mobility in soil

**Mobility** No data available.

## 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

## 12.6. Other adverse effects

**Other adverse effects** None known.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**General information** Dispose of waste product or used containers in accordance with local regulations Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

**Disposal methods** Containers should be thoroughly emptied before disposal because of the risk of an explosion. Do not pierce or burn, even after use.

**Waste class** The waste code classification is to be carried out according to the European Waste Catalogue (EWC).

## SECTION 14: Transport information

### 14.1. UN number

**UN No. (ADR/RID)** 1950

**UN No. (IMDG)** 1950

**UN No. (ICAO)** 1950

**UN No. (ADN)** 1950

### 14.2. UN proper shipping name

**Proper shipping name (ADR/RID)** AEROSOLS, FLAMMABLE

**Proper shipping name (IMDG)** AEROSOLS, FLAMMABLE

**Proper shipping name (ICAO)** AEROSOLS, FLAMMABLE

**Proper shipping name (ADN)** AEROSOLS, FLAMMABLE

### 14.3. Transport hazard class(es)

**ADR/RID class** 2.1

**ADR/RID classification code** 5F

**ADR/RID label** 2.1

## HOTSPOT Black Paint Aerosols

IMDG class	2.1
ICAO class/division	2.1
ADN class	2.1

### Transport labels



### 14.4. Packing group

Not applicable.

### 14.5. Environmental hazards

#### Environmentally hazardous substance/marine pollutant

No.

### 14.6. Special precautions for user

EmS F-D, S-U

ADR transport category 2

Tunnel restriction code (D)

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**National regulations** The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).

**EU legislation** Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).  
 Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).  
 Council Directive of 20 May 1975 on the approximation of the laws of the Member States relating to aerosol dispensers (75/324/EEC) (as amended).  
 Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste.

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

## SECTION 16: Other information

Revision date	11/02/2019
Revision	2
Supersedes date	24/01/2019
SDS number	7737

## HOTSPOT Black Paint Aerosols

### Hazard statements in full

H220 Extremely flammable gas.  
H222 Extremely flammable aerosol.  
H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H229 Pressurised container: may burst if heated.  
H280 Contains gas under pressure; may explode if heated.  
H302 Harmful if swallowed.  
H304 May be fatal if swallowed and enters airways.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.