



**SAFETY DATA SHEET**  
**HOTSPOT BRICK AND STONE SEALER**

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

**Product name** HOTSPOT BRICK AND STONE SEALER

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Identified uses** Sealer.

**1.3. Details of the supplier of the safety data sheet**

**Supplier** Rustins Ltd  
Waterloo Road  
London  
NW2 7TX  
United Kingdom

**1.4. Emergency telephone number** +44 (0)20 8450 4666 (Hours 09:00 - 17:00 Mon to Fri)

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification**

**Physical hazards**

Not Classified

**Health hazards**

Not Classified

**Environmental hazards**

Not Classified

**Classification (67/548/EEC or 1999/45/EC)**

R10.

**2.2. Label elements**

**2.3. Other hazards**

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

1-METHOXY-2-PROPANOL	60-100%
CAS number: 107-98-2 EC number: 203-539-1	
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>
Flam. Liq. 3 - H226	R10 R67
STOT SE 3 - H336	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

**SECTION 4: First aid measures**

## HOTSPOT BRICK AND STONE SEALER

### 4.1. Description of first aid measures

#### **Inhalation**

In the event of any sensitisation symptoms developing, ensure further exposure is avoided. Get medical attention immediately.

#### **Ingestion**

DO NOT induce vomiting. Get medical attention immediately.

#### **Skin contact**

Wash with plenty of water.

#### **Eye contact**

If liquid has entered the eyes, proceed as follows. Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Continue to rinse for at least 15 minutes. Get medical attention if symptoms are severe or persist after washing.

### 4.2. Most important symptoms and effects, both acute and delayed

#### **General information**

See Section 11 for additional information on health hazards.

### 4.3. Indication of any immediate medical attention and special treatment needed

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### **Suitable extinguishing media**

Use alcohol-resistant foam, carbon dioxide or dry powder to extinguish.

#### **Unsuitable extinguishing media**

Do not use water jet as an extinguisher, as this will spread the fire.

### 5.2. Special hazards arising from the substance or mixture

#### **Specific hazards**

The product is flammable. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Risk of explosion if heated under confinement.

### 5.3. Advice for firefighters

#### **Protective actions during firefighting**

In case of fire: Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Do not use water jet as an extinguisher, as this will spread the fire. Avoid breathing fire gases or vapours. Control run-off water by containing and keeping it out of sewers and watercourses. Containers can burst violently or explode when heated, due to excessive pressure build-up.

#### **Special protective equipment for firefighters**

Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### **Personal precautions**

No smoking, sparks, flames or other sources of ignition near spillage. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Send away individuals who are not suitably equipped.

### 6.2. Environmental precautions

#### **Environmental precautions**

Absorb on inert material and dispose by incineration or by depuration plant. Do not discharge into drains or watercourses or onto the ground.

### 6.3. Methods and material for containment and cleaning up

#### **Methods for cleaning up**

## HOTSPOT BRICK AND STONE SEALER

Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Cover large spillages with alcohol-resistant foam. Small Spillages: Absorb small quantities with paper towels and evaporate in a safe place. Once evaporation is complete, place paper in a suitable waste disposal container and seal securely. Large Spillages: Absorb in vermiculite, dry sand or earth and place into containers. Containers with collected spillage must be properly labelled with correct contents and hazard symbol. Dispose of contents/container in accordance with local regulations. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate.

### **6.4. Reference to other sections**

#### **Reference to other sections**

Wear protective clothing as described in Section 8 of this safety data sheet. For waste disposal, see Section 13.

## **SECTION 7: Handling and storage**

### **7.1. Precautions for safe handling**

#### **Usage precautions**

Read label before use. For personal protection, see Section 8. Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Avoid breathing vapour/spray. During application and drying, solvent vapours will be emitted. Materials such as cleaning rags and paper wipes that are contaminated with flammable liquids may self-ignite after use and should be stored in designated fireproof containers with tight-fitting, self-closing lids. Observe any occupational exposure limits for the product or ingredients. This product is not to be used under conditions of poor ventilation. Provide adequate ventilation. If ventilation is inadequate, suitable respiratory protection must be worn. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid spilling. Avoid release to the environment. Do not eat, drink or smoke when using this product. Wash contaminated skin thoroughly after handling. Wash contaminated skin thoroughly after handling. Wash skin thoroughly after handling. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. When handled correctly, undamaged units represent no danger.

### **7.2. Conditions for safe storage, including any incompatibilities**

#### **Storage precautions**

Store in tightly-closed, original container in a dry and cool place. Keep away from heat, sparks and open flame. Do not store near heat sources or expose to high temperatures. Use appropriate containment to avoid environmental contamination. Only store in correctly labelled containers.

### **7.3. Specific end use(s)**

#### **Specific end use(s)**

The identified uses for this product are detailed in Section 1.2.

## **SECTION 8: Exposure Controls/personal protection**

### **8.1. Control parameters**

#### **Occupational exposure limits**

##### **1-METHOXY-2-PROPANOL**

Long-term exposure limit (8-hour TWA): WEL 100 ppm(Sk) 375 mg/m<sup>3</sup>(Sk)

Short-term exposure limit (15-minute): WEL 150 ppm(Sk) 560 mg/m<sup>3</sup>(Sk)

WEL = Workplace Exposure Limit

### **8.2. Exposure controls**

#### **Eye/face protection**

Personal protective equipment for eye and face protection should comply with European Standard EN166.

#### **Hand protection**

To protect hands from chemicals, gloves should comply with European Standard EN374. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected.

#### **Other skin and body protection**

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Wear appropriate clothing to prevent repeated or prolonged skin contact. Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.

## HOTSPOT BRICK AND STONE SEALER

### SECTION 9: Physical and Chemical Properties

#### 9.1. Information on basic physical and chemical properties

**Appearance**

Light liquid

**Colour**

Colourless to pale yellow.

**Odour**

Solvent.

**Initial boiling point and range**

160-190°C @

**Flash point**

45°C

**Relative density**

0.918 @ °C

**Solubility(ies)**

Insoluble in water.

#### 9.2. Other information

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

The reactivity data for this product will be typical of those for the following class of materials: Alcohols, glycols. See Section 10.3 (Possibility of hazardous reactions) for further information.

#### 10.2. Chemical stability

**Stability**

Stable at normal ambient temperatures and when used as recommended.

#### 10.3. Possibility of hazardous reactions

The following materials may react strongly with the product: Strong acids. Oxidising agents.

#### 10.4. Conditions to avoid

Avoid contact with strong oxidising agents. Heating may cause a fire or explosion. Do not pressurise, cut, weld, drill, grind or otherwise expose containers to heat or sources of ignition. Avoid the following conditions: Heat, sparks, flames. The following materials may react strongly with the product: Strong acids. Oxidising agents.

#### 10.5. Incompatible materials

**Materials to avoid**

Avoid contact with the following materials: Strong acids. Oxidising agents.

#### 10.6. Hazardous decomposition products

Heating may generate flammable vapours.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

**Toxicological effects**

TLV-TWA: 1 Methoxy-2-propanol : 369 mg/m<sup>3</sup> (ACGIH) In normal use conditions, significant values in the air are not reduced.  
LCLo for aliphatic hydrocarbons: 10 mg/m<sup>3</sup>/2.5 hours.

### SECTION 12: Ecological Information

#### 12.1. Toxicity

#### 12.2. Persistence and degradability

**Persistence and degradability**

The product does not contain any surfactant.

## HOTSPOT BRICK AND STONE SEALER

### 12.3. Bioaccumulative potential

### 12.4. Mobility in soil

### 12.5. Results of PBT and vPvB assessment

### 12.6. Other adverse effects

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

#### General information

Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

## **SECTION 14: Transport information**

### 14.1. UN number

UN No. (ADR/RID)	3092
UN No. (IMDG)	3092
UN No. (ICAO)	3092

### 14.2. UN proper shipping name

Proper shipping name (ADR/RID)	1-METHOXY-2-PROPANOL
Proper shipping name (IMDG)	1-METHOXY-2-PROPANOL
Proper shipping name (ICAO)	1-METHOXY-2-PROPANOL
Proper shipping name (ADN)	1-METHOXY-2-PROPANOL

### 14.3. Transport hazard class(es)

ADR/RID class	3
ADR/RID subsidiary risk	
ADR/RID label	3
IMDG class	3
IMDG subsidiary risk	
ICAO class/division	3
ICAO subsidiary risk	
Transport labels	

### 14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III
ICAO packing group	III

### 14.5. Environmental hazards

### 14.6. Special precautions for user

EmS	F-E, S-D
Emergency Action Code	•2Y

## HOTSPOT BRICK AND STONE SEALER

Hazard Identification Number 30  
(ADR/RID)

Tunnel restriction code (D/E)

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

#### **SECTION 15: Regulatory information**

##### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

###### **EU legislation**

Dangerous Preparations Directive 1999/45/EC. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

##### 15.2. Chemical safety assessment

#### **SECTION 16: Other information**

Revision date 07/01/2015

Revision 1

SDS number 10403

###### **Risk phrases in full**

R10 Flammable.

R67 Vapours may cause drowsiness and dizziness.

###### **Hazard statements in full**

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

#### Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.