



SAFETY DATA SHEET

Page 1 of 4

FG5429-720 Platinum Series Renovating Cockpit Shine

Revision 3
Revision date 14-Jan-2010

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

Product name FG5429-720 Platinum Series Renovating Cockpit Shine

Company Turtle Wax Limited
East Gillibrands
Skelmersdale
Lancashire
WN8 9TX
England
MSDS@turtlewax.ltd.uk
www.turtlewaxeurope.com

Telephone +44 (0)1695 722161

Fax +44 (0)1695 716621

Emergency telephone number +44 (0)1695 722161 (Daytime)

Intended use Car Care Product.

2 HAZARDS IDENTIFICATION.

Main hazards Harmful: may cause lung damage if swallowed. Extremely flammable. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Vapours may cause drowsiness and dizziness.

3 . COMPOSITION / INFORMATION ON INGREDIENTS.

Hazardous ingredients

	Conc.	CAS	EINECS	Symbols/Risk phrases
Butane	15-30%	106-97-8	203-448-7	F+; R12
Isopropanol (Propan-2-ol)	5-10%	67-63-0	200-661-7	F; R11 Xi; R36 R67
Naptha Solvent Refined	5-10%	64741-84-0	265-086-6	F;R11 N;R51/53 Xn;R65 R67
Naptha Hydrotreated Light	5-10%	64742-49-0	265-151-9	Xn; R65 Xi; R38 N; R51/53 R10-66-67

4. FIRST AID MEASURES

Skin contact May cause irritation to skin. Wash off immediately with plenty of soap and water.
Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.

Eye contact May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.

Inhalation Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention.

Ingestion Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist.

General information In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

Print date 14-Jan-2010

FG5429-720 Platinum Series Renovating Cockpit Shine

Revision 3

Revision date 14-Jan-2010

5. FIRE FIGHTING MEASURES

Extinguishing media	Carbon dioxide (CO ₂) Alcohol resistant foam.
Fire hazards	Vapour may travel considerable distance to source of ignition and flash back.
Protective equipment	Wear suitable respiratory equipment when necessary.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions	Ensure adequate ventilation of the working area. Evacuate personnel to a safe area. Eliminate all sources of ignition. Wear suitable protective equipment.
Environmental precautions	Do not allow product to enter drains. Prevent further spillage if safe.
Clean up methods	Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

7. HANDLING AND STORAGE

Handling	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking.
Storage	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits

Butane	WEL 8-hr limit ppm: 600	WEL 8-hr limit mg/m ³ : 1450
	WEL 15 min limit ppm: 750	WEL 15 min limit mg/m ³ : 1810
Isopropanol (Propan-2-ol)	WEL 8-hr limit ppm: 400	WEL 8-hr limit mg/m ³ : 999
	WEL 15 min limit ppm: 500	WEL 15 min limit mg/m ³ : 1250

Engineering measures	Ensure adequate ventilation of the working area.
Respiratory protection	Wear suitable respiratory equipment when necessary.
Hand protection	Chemical resistant gloves (PVC)
Eye protection	Approved safety goggles.
Protective equipment	Wear chemical protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Description	Aerosol.
Colour	Colourless.
Odour	Characteristic.
Boiling point	35°C
Flash point	-2°C
Evaporation rate	<0.1 n-butyl acetate = 1.0

10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions.
Conditions to avoid	Heat, sparks and open flames.
Materials to avoid	None.
Hazardous decomposition products	None.

11. TOXICOLOGICAL INFORMATION

Toxicological information	No known adverse health effects.
----------------------------------	----------------------------------

FG5429-720 Platinum Series Renovating Cockpit Shine

Revision 3
Revision date 14-Jan-2010

12. ECOLOGICAL INFORMATION

Ecotoxicity May cause long-term adverse effects in the aquatic environment.
Bioaccumulation Does not bioaccumulate.

13. DISPOSAL CONSIDERATIONS

General information Dispose of in compliance with all local and national regulations.
Disposal of packaging Empty containers can be sent for disposal or recycling.

14. TRANSPORT INFORMATION

ADR/RID Shipped in limited quantities under ADR.

UN 1950 **Packing group** -
Class 2 **Hazard ID** -
Proper Shipping Name AEROSOLS .

IMDG

UN 1950 **Packing group** -
Class 2 **Marine pollutant** .
EmS Code F-D S-U

IATA

UN 1950 **Packing group** -
Class 2 **Subsidiary risk** see SP63

15. REGULATORY INFORMATION

Labelling The product is classified in accordance with 67/548/EEC.

Symbols F+ - Extremely flammable



Risk phrases R12 - Extremely flammable.
R52/53 - Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R67 - Vapours may cause drowsiness and dizziness.

Safety phrases S2 - Keep out of the reach of children.
S16 - Keep away from sources of ignition - No smoking.
S23 - Do not breathe gas/fumes/vapour/spray.
S51 - Use only in well-ventilated areas.

Further information Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50 °C.
Do not pierce or burn, even after use.
Do not spray on a naked flame or any incandescent material.
Safety data sheet available for professional user on request.

FG5429-720 Platinum Series Renovating Cockpit Shine

Revision 3

Revision date 14-Jan-2010

16. OTHER INFORMATION

Text of risk phrases in

R10 - Flammable.

Section 3.

R11 - Highly flammable.

R12 - Extremely flammable.

R36 - Irritating to eyes.

R38 - Irritating to skin.

R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 - Harmful: may cause lung damage if swallowed.

R66 - Repeated exposure may cause skin dryness or cracking.

R67 - Vapours may cause drowsiness and dizziness.

Further information

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.

Revision

This document differs from the previous version in the following areas:

15 - symbols.