

FG8MS Wireless Glass Break Sensor



KEY FEATURES AND BENEFITS

- Honeywell unique patented bi-directional secure 868 MHz Wireless Technology - longer range (1000m) and improved battery performance.
- Fast fit and simple setup: ready to go out of the box with screw-free install. Low battery indication.

PRODUCT SPECIFICATION

Languages covered –
GB, DE, FR, NL, ES, PT, IT = English, German, French, Dutch, Spanish, Portuguese, Italian

- Colour - White
- Frequency - 868MHz
- Detection Range – up to 7.6m
- Glass Type - plate, tempered, laminated, wired, coated, sealed insulating.
- Test Mode – Yes
- Anti-Tamper protection – Yes
- Battery Life - 7 years
- Low Battery Indicator - Yes

KIT CONTENTS

- 1 x Wireless Glass Break Sensor fitted with batteries and battery isolation tab and hinge cover
- 1 x Quick start Installation guide
- 1 x Declaration of conformity

INSTALLATION

- Internal use only
- With captive mounting hole & hinged cover

MECHANICAL & ENVIRONMENTAL:

Temperature:	
Operating:	-10°C to +55°C
Storage:	-20°C to +55°C
Dimensions:	127 x 77 x 24mm (HxWxD)
Product Weight:	143g (exc batteries)

POWER SUPPLY:

2 x 3V CR123 Lithium batteries

PERFORMANCE:

Alarm Interface:

RF operating frequency:	868MHz												
RF range:	1000m (Open field)												
Supervision time:	18 minutes												
Transmitter test mode:	Activated when powered on. Deactivated 10 minutes after tamper closed												
Glass Break test mode:	Activated when powered on, by button or by glass break tester. Deactivated 5 minutes after last tester sound												
Glass thickness:	<table> <tr> <td>Plate</td> <td>: 2mm to 10mm</td> </tr> <tr> <td>Tempered</td> <td>: 3mm to 10mm</td> </tr> <tr> <td>Laminated</td> <td>: 3mm to 14mm</td> </tr> <tr> <td>Wired</td> <td>: 6mm</td> </tr> <tr> <td>Coated</td> <td>: 3mm to 6mm</td> </tr> <tr> <td>Sealed Insulating:</td> <td>3mm to 6mm</td> </tr> </table>	Plate	: 2mm to 10mm	Tempered	: 3mm to 10mm	Laminated	: 3mm to 14mm	Wired	: 6mm	Coated	: 3mm to 6mm	Sealed Insulating:	3mm to 6mm
Plate	: 2mm to 10mm												
Tempered	: 3mm to 10mm												
Laminated	: 3mm to 14mm												
Wired	: 6mm												
Coated	: 3mm to 6mm												
Sealed Insulating:	3mm to 6mm												

Note: Glass must be framed in wall or mounted in barrier with >0.9m wide

PACKAGING DATA

SINGLE PRODUCT

EAN code:	5004100969521
Pack weight:	approx. 177g
Pack dimension:	215 x 150 x 40mm

STANDARD PACK

Quantity:	6
-----------	---